

# USSD 200 Price List

**SAN**

Ready



**SCSI**

Q2-2008

10µs access time

Part #	USSD 200 Standard Configuration	GB	List Price in US\$
U-3202-16	USSD - SCSI 320MB/s, 2 Port	16	\$18,000
U-3202-32	USSD - SCSI 320MB/s, 2 Port	32	\$28,000
U-3202-64	USSD - SCSI 320MB/s, 2 Port	64	\$49,000
U-SA02-16	USSD - SAS 3Gb/s, 2 Port	16	\$18,000
U-SA02-32	USSD - SAS 3Gb/s, 2 Port	32	\$28,000
U-SA02-64	USSD - SAS 3Gb/s, 2 Port	64	\$49,000
U-SA02-128	USSD - SAS 3Gb/s, 2 Port	128	\$75,000
U-SA02-256	USSD - SAS 3Gb/s, 2 Port	256	Call
U-F402-16	USSD - FC 4Gb/s, 2 Port	16	\$18,000
U-F402-32	USSD - FC 4Gb/s, 2 Port	32	\$28,000
U-F402-64	USSD - FC 4Gb/s, 2 Port	64	\$49,000
U-F402-128	USSD - FC 4Gb/s, 2 Port	128	\$75,000
U-F402-256	USSD - FC 4Gb/s, 2 Port	256	Call

- Pricing, specifications, availability, terms and conditions are subject to change without notice
- The prices shown do not include any taxes, import or export duties, tariffs, custom charges or insurance
- Payment terms are payment in advance unless otherwise agreed in writing. All shipments will be made factory F.O.B.

## New Model USSD 200

Our latest product generation – the USSD 200 – has a 2U rack mount form factor, a maximum storage capacity of 128 GB, and supports up to 3.6 GB/s aggregated bandwidth via multi FC links. The capacity can be scaled up by linking USSD devices in 19" rack cabinets. USSD supports virtually all connectivity options on the market including 320 MB/s SCSI-3 Ultra-Wide LVD, 3 Gb/s SAS and 4 Gb/s Fibre Channel interfaces. Connectivity can be rapidly modified and adapted to your data center's evolving requirements. USSD supports resource leveraging where multiple host computers share USSD capacity. It is an ideal resource in switched fabric environments (SAN) for processing frequently accessed data.

USSD is a plug-and-play device that appears as a conventional SCSI or Fibre Channel disk drive to the host computer's operating system and supports all major operating systems. The new USSD 200 includes expanded USSD management utilities. Reliability is assured by USSD's sole use of standard industry components of proven performance and reliability and its assembly by a world-class, ISO 9001:2000 certified manufacturer-integrator. Features include: hot swappable redundant power supply (2 Power Input Sources); redundant fans; up to 4 hot swappable data retention HDDs; Error Detection/Correction (64 bytes dedicated per 512 bytes sector), Chipkill. USSD is covered by a three year warranty.

Contact us at [info@solidaccess.com](mailto:info@solidaccess.com) or call 978 463 0642 for more information

Solid Access Technologies LLC, Corporate Office, 27 Green Street, Newburyport, MA 01950, USA

☎ 978 463 0642

www. **SOLIDACCESS** .com

📄 978 463 7480